V7 L17GM

Value Line

Specifications

Panel Size	17” (~ 432 mm)
Aspect Ratio	5:4 (~ 338 x 270 mm)
Panel Specification	Panel TN
Recommended Resolution	1280 x 1024
Pixel Pitch	0.264 mm
Colours max.	16.2 Mio
Brightness typ.	300 cd/m²
Contrast Ratio typ.	500:1
Viewing Angle H/V	150°/135°
Response Time typ.	8 ms
Features	speakers, Kensington® security port, internal power supply, silver-black design
Adjustment	Bightness, Contrast, Auto-Adjust, Clock, Phase, H/V-Position, Sharpness, Colour Control, OSD Position, Audio Control, Language, Recall etc.
Frequency at Resolution	640 x 480 @ 75 Hz 800 x 600 @ 75 Hz 1024 x 768 @ 75 Hz 1280 x 1024 @ 75 Hz
Horizontal Frequency	30 - 80 kHz
Vertical Frequency	56 - 75 Hz
Videobandwidth	135 Mhz
Input Signal	RGB Analog
Input Terminal	15pin D-Sub
Plug & Play	VESA DDC 2B
Power Management	VESA DPMS
Power Consumption On/Off	36/1 Watt max.
Power Requirements	AC 100 - 240V, 50/60 Hz
Dimensions WxHxD **with stand** **packaging**	 379 x 386 x 197 mm 438 x 516 x 110 mm
Weight with stand **incl. packaging**	3.6 kg 4.7 kg
Tilt	-5° ~ 20°
Wallmountable	VESA 100 x 100 mm
Certifications & Standards	CE, TUV/GS, FCC, UL, TCO´03, ISO 13406-2
Supplied Accessories	12 languages manual CD, quick instruction guide, power cable, VGA cable, audio cable
Pixel Criteria	bright <= 3, dark <= 3, total <= 7
Service	3 years on-site

The data in this publication is for illustration purposes only and does not necessarily represent standards or specifications which must be met by V7. Design and specifications are subject to change without prior notice. Trademarks belong to their respective owners. No responsibility assumed and all liability for damages resulting from use of this information or for any errors or omissions are disclaimed. Measurement standards and testing conditions as per manufacturer definitions, available on request.
Issue: 02/2006